

Outdoor Wideband Reactive Power Splitter

PM-AS-PS-KH2-ON300C55-HT, PM-AS-PS-KH3-ON300C55-HT,
PM-AS-PS-KH4-ON300C55-HT

2/3/4ways, 698-4000MHz, N-Female, 300W

Electrical Specifications

Parameters	Unit	Specifications		
		PM-AS-PS-KH2-ON300C55-HT	PM-AS-PS-KH3-ON300C55-HT	PM-AS-PS-KH4-ON300C55-HT
		2 Ways	3 Ways	4 Ways
Frequency Range	MHz	698-4000		
Splitting Loss	dB	3.0	4.8	6.0
Insertion Loss	dB	≤0.4	≤0.5	≤0.6
Input Port VSWR		≤1.3	≤1.3	≤1.4
PIM3 at 2x43 dBm	dBc	≤-155		
Impedance	Ω	50		
Input Average Power, Maximum	W	300		
Peak Power	W	1000		

Mechanical Specifications

Parameters	Unit	Specifications		
Product Dimension, HxWxD	mm	213.3x52x25	246.4x52x25	246.4x52x25
Product Weight	kg	0.15	0.18	0.20
Connector Type		N-Female		
Appearance		Black		
Operational Temperature	°C	-25~+65		
Operational Humidity	%	≤95		
Environmental Protection		IP65		

Outline Drawing

