

PRODUCT DESCRIPTION



- The high-performance of attenuation allows coaxial cable to be used in different RF systems.
- Wide range of applications, such as indoor distribution, broadcast, various base stations, wireless cellular, and others.
- Lower VSWR, perfect shielding effectiveness, and extraordinary inter-modulation performance lead to fewer energy loss and outer interference.

CONSTRUCTION

Inner conductor	Copper Clad Aluminum	$\Phi 4.80 \pm 0.05 \text{mm}$
Insulation	Physically foamed PE	$\Phi 12.20 \pm 0.20 \text{mm}$
Outer conductor	Ring corrugated copper	$\Phi 13.70 \pm 0.20 \text{mm}$
Jacket	Black PE or Flame Retardant PE	$\Phi 15.40 \pm 0.20 \text{mm}$

MECHANICAL PROPERTIES

Min. single bending radius	mm	70
Min. repeated bending radius	mm	125
Maximum tensile strength	N	≥ 1130
Recommended maximum clamp spacing	m	1

ELECTRICAL PROPERTIES

Impedance	Ω	50 ± 3
Nominal capacitance	pF/m	76
Nominal inductance	$\mu\text{H/m}$	0.19
Propagation velocity	%	86
DC breakdown voltage	kV	4.0
Insulation resistance	$\text{M}\Omega \cdot \text{km}$	> 5000
Peak power rating	kW	40
Cut-off frequency	GHz	8.8

TRANSMISSION PROPERTIES

Frequency MHz	Attenuation @20°C, dB/100m(dB/100ft)	Power @40°C, kW
100	2.17(0.66)	3.49
450	4.75(1.45)	1.59
690	5.97(1.82)	1.34
800	6.46(1.97)	1.17
900	6.85(2.09)	1.10
1000	7.28(2.22)	1.04
1800	10.10(3.08)	0.75
2000	10.70(3.26)	0.71
2200	11.24(3.43)	0.65
2400	11.78(3.59)	0.62
2500	12.06(3.68)	0.61
2600	12.34(3.76)	0.60
2700	12.61(3.84)	0.59
3000	13.40(4.09)	0.57
3300	14.15(4.31)	0.54
3400	14.40(4.39)	0.53
3500	14.64(4.46)	0.52
3600	14.88(4.54)	0.51
3800	15.36(4.68)	0.50

Attenuation values may be with a tolerance of 5%.

VSWR

690-960MHz	≤	1.13
1700-2200MHz	≤	1.15
2300-2400MHz	≤	1.15
2500-2690MHz	≤	1.15
3300~3800MHz	≤	1.25

ENVIRONMENTAL PROPERTIES

		PE jacket	LSZH
Recommended storage temperature	°C	-55~+85	-30~+80
Recommended installation temperature	°C	-40~+60	-25~+60
Recommended operating temperature	°C	-55~+85	-30~+80
2011/65/EU(ROHS)		compliant	compliant