



APTEK AP1115-20B

10&100&1000M Media Converter Datasheet

- In accordance with Ethernet standards IEEE802.3 10/100Base-TX/1000Base-TX and 1000Base-FX
- Supported Ports: SC for optical fiber; RJ45 for twisted pair
- Auto-adaptation rate and full/half-duplex mode supported at twisted pair port
- Auto MDI/MDIX supported without need of cable selection
- Up to 6 LEDs for status indication of optical power port and UTP port
- External and built-in DC power supplies provided
- Conflicting frames detection in half-duplex and flow control in full duplex supported



APTEK AP1115-20B is Gigabit Ethernet used for optical transmission via high-speed Ethernet. It is capable of switching between twisted pair and optical and relaying across 10/100 Base-TX/1000 Base-TX and 1000Base-FX network segments, meeting long-distance, high-speed and high-broadband fast Ethernet workgroup users' needs, achieving high-speed remote interconnection for up to 20 km's relay-free computer data network. With steady and reliable performance, design in accordance with Ethernet standard and lightning protection, it is particularly applicable to a wide range of fields requiring a variety of broadband data network and high-reliability data transmission or dedicated IP data transfer network, such as telecommunication, cable television, railway, military, finance and securities, customs, civil aviation, shipping, power, water conservancy and oilfield etc, and is an ideal type of facility to build broadband campus network, cable TV and intelligent broadband FTTB/FTTH networks

Technical Parameters

Technical Parameters for 10/100M Adaptive Fast Ethernet Optical Media Converter	
Number of Network Ports	1 channel
Number of Optical Ports	1 channel
NIC Transmission Rate	10/100/1000 Mbit/s
NIC Transmission Mode	10/100/1000M adaptive with support for automatic inversion of MDI/MDIX
Optical Port Transmission Rate	1000Mbit/s
Operating Voltage	AC 220V
Overall Power	<3W
Network Ports	RJ45 port
Optical Specifications	Optical Port: SC Single-Mode Wavelength: TX 1550/ RX 1310nm Optical Power (dBm): -8 ~ -3 Receiving Sensitivity (dBm): -24 Transmission Range (km): 20 Km
Data Channel	IEEE802.3x and collision base backpressure supported
Working Mode	Full/half duplex supported
Transmission Rate	1000Mbit/s with error rate of zero



Operating Environment

1. Operating Voltage	AC 220V	
2. Operating Humidity	Operating Temperature:	0°C to +55°C
	Storage Temperature:	-20°C to +70°C
	Humidity:	5% to 90%

Quality Assurance

MTBF > 100,000 hours
 Replacement within one year and non-charge repair within three years guaranteed

Application Fields


- For intranet prepared for expansion from 100M to 1000M
- For integrated data network for multimedia such as image, voice and etc.
- For point-to-point computer data transmission
- For computer data transmission network in a wide range of business application
- For broadband campus network, cable TV and intelligent FTTB/FTTH data tape
- In combination with switchboard or other computer network facilitates for: chain-type, star-type and ring-type network and other computer networks

Remarks and Notes

Instructions on Front Panel : Identification for front panel of the media converter is shown below

a.	Identification of Media Converter	TX - transmitting terminal; RX - receiving terminal;
b.	PWR	Power Indicator Light "ON" means normal operation of DC 5V power supply adaptor.
c.	1000M Indicator Light	"ON" means the rate of the electric port is 1000 Mbps, while "OFF" means the rate is 100 Mbps.
d.	LINK/ACT (FP)	"ON" means connectivity of the optical channel; "FLASH" means data transfer in the channel; "OFF" means non-connectivity of the optical channel.
e.	LINK/ACT (TP)	"ON" means connectivity of the electric circuit; "FLASH" means data transfer in the circuit; "OFF" means non-connectivity of the electric circuit.

Mounting Dimensions Sketch



Product Connection Diagram

